

What is claimed is

- SWB
A/
- 1 1. A golf club head comprising:
2 a cast head body constituted by a hollow outer shell;
3 said hollow outer shell defining a top portion, a sole
4 portion, a heel wall and a toe portion;
5 a shaft securing portion formed adjacent to said heel wall
6 and extended from said top portion to said sole portion; and
7 a first hollow portion formed between said shaft securing
8 portion and said heel wall of said head body.
- 1 2. A golf club head according to claim 1, wherein said hollow
2 outer shell defines a face opening portion, a face portion is
3 fixed to said face opening portion.
- 1 3. A golf club head according to claim 2, wherein a second
2 hollow portion is formed between said shaft securing portion
3 and said face portion.
- 1 4. A golf club head according to claim 2, wherein said face
2 portion is formed by forging.
- 1 5. A golf club head according to claim 2, wherein said face
2 portion is formed by press working of a rolled plate member.

1 6. A golf club head according to claim 1, wherein a shaft
2 securing hole penetrates said shaft securing portion in a region
3 from said top portion to said sole portion.

1 7. A golf club head according to claim 1, wherein said shaft
2 securing hole of said shaft securing portion has a bottom
3 portion.

1 8. A golf club head according to claim 7, wherein said bottom
2 portion is formed in a same surface of said sole portion of
3 said head body.

1 9. A golf club head according to claim 7, wherein said bottom
2 portion of said shaft securing hole has substantially the same
3 thickness as the thickness of said sole portion.

1 10. A golf club head according to claim 1, wherein said hollow
2 outer shell and said shaft securing portion are integrally
3 molded with each other by precise casting.

1 11. A golf club head according to claim 1, wherein said shaft
2 securing portion is formed into a cylindrical shape from said
3 top portion to said sole portion.

1 12. A golf club head according to claim 1, wherein said first
2 hollow portion is formed such that a clearance of 1 mm to 10

3 mm is defined between said shaft securing portion and said heel
4 wall.

1 13. A golf club head according to claim 1, wherein said heel
2 wall has a thickness of 0.3 mm to 2 mm.

1 14. A golf club head according to claim 1, wherein a width
2 of said first hollow portion adjacent to said sole portion is
3 wider than a width of said first hollow portion adjacent to
4 said top portion.

Sub
AB
1 15. A golf club head according to claim 1, wherein an edge
2 is formed between said sole portion and said heel wall. at a
3 heel side near than at least said shaft securing portion.

1 16. A golf club head according to claim 1, wherein a first
2 upper end of the inside portion of said toe portion is higher
3 than a second upper end of the inside portion of said heel
4 portion in a cross section passing through an axis of said shaft
5 securing hole and along said face portion.

1 17. A golf club head according to claim 1, wherein a support
2 portion connects said shaft securing portion and said heel wall.

1 18. A golf club head according to claim 1, wherein a hosel
2 portion is formed at said top portion of said head body by
3 projecting said shaft securing portion from said top portion.

8
43
1 19. A Golf club head according to claim 1, wherein an upper
2 end portion of said shaft securing portion is provided lower
3 than a top of said top portion.

1 20. A golf club head according to claim 1, wherein said head
2 body is formed from β -type titanium alloy.

1 21. A golf club head according to claim 2, wherein said head
2 body is formed from $\alpha\beta$ -type titanium alloy, and said face
3 portion is formed from β -type titanium alloy.

1 22. A method of manufacturing a cast head body of a hollow
2 golf club head including a shaft securing portion extending
3 from a top portion to a sole portion and a hollow portion between
4 said shaft securing portion and a heel wall, wherein a mold
5 piece for forming said hollow portion is interposed between
6 portions corresponding respectively to said shaft securing
7 portion and said heel wall.

1 23. A method of manufacturing a head body of a hollow golf
2 club head according to claim 22, wherein said mold piece is
3 formed integrally with a lower head body mold member for molding
4 an outside of said head body.

1 24. A method of manufacturing a head body of a hollow golf
2 club head according to claim 22, wherein said mold piece is

3 individual from a lower head body mold member for molding an
4 outside of said head body.

1 25. A method of manufacturing a head body of a hollow golf
2 club head according to claim 24, wherein said mold piece
3 includes a face mold piece and a back mold piece, said face
4 mold piece molds said hollow portion adjacent to a face opening
5 portion, and said back mold piece located to a rear side of
6 said face mold piece.

1 26. A method of manufacturing a head body of a hollow golf
2 club head according to claim 24, wherein a hole or a cut portion
3 for extracting said mold piece is formed in said head body to
4 be manufactured, and said mold piece is extracted in a direction
5 through said hole or said cut portion, said direction is
6 different from a direction of at least one core for molding
7 said head body extracted.

1 27. A method of manufacturing a head body of a hollow golf
2 club head according to claim 22, wherein said mold piece is
3 fractured or dissolved when said mold piece is extracted.

Sub
A4 1 28. A golf club head comprising:
2 a head body constituted by a hollow outer shell;
3 a shaft securing portion, provided with at least one of
4 a top portion and a sole portion, formed by cast, ?
5 the other of said top portion and said sole portion fixed

6 to said one of said top portion and said sole portion;
7 wherein a hollow portion is provided between said hollow
8 portion and a heel portion.

1 29. A golf club head according to claim 28, wherein a joining
2 hole, for joining said shaft securing portion, is provided with
3 the other of said top portion and said sole portion.

4